



主轴静载  
**static load**  
2000 kg

最大载重  
**load**  
450 kg

最大速度  
**speed**  
up to 1 m/s

曳引轮  
**sheave**  
85 - 100 mm

自重  
**weight**  
90 kg

额定扭矩 <b>Nominal Torque</b>	极数 <b>Poles</b>	编码器 <b>Encoder</b>	钢带轮 <b>Belt Pulley</b>		
			宽度 Width	钢带数 min - max	槽距 Pitch
<b>Nm</b>			mm	n°	mm
<b>74 S5 - 25% ED 180 s/h</b>	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531	60 55	2	65
<b>制动器 Brake</b>					
EMFR DC110V/1.4A[2X125Nm] EMFS125 2XDC110V/2X0.76A[2X135N.m] CE Certified					

- 1 - 以上数据是以平衡系数为45%的基础上计算出来的理论数据  
1 - The values are obtained considering system balanced at the 45%
- 2 - 数据如有更改，恕不另行通知  
2 - Data are subject to change without prior notice

2:1	额定载重 Load	额定速度 Speed	曳引轮 Sheave				额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V
			Ø	宽度 Width	n°	槽距 Pitch						
	kg	m/s	mm	mm		mm	Nm	kW	RPM	Hz	A	A
320	0,40	0,40	100	60	2	65	51	0,81	153	20,4	5,1	3,3
								1,02	191	25,5	6,5	3,3
								1,28	241	32,1	7,1	3,3
								2,03	382	50,9	9,4	5,1
400	0,40	0,50	100	60	2	65	66	1,05	153	20,4	6,6	4,3
								1,32	191	25,5	6,6	4,3
								1,66	241	32,1	8,5	4,3
								2,63	382	50,9	12,2	6,6
450	0,40	0,50	100	60	2	65	71	1,14	153	20,4	7,1	4,5
								1,43	191	25,5	9,1	4,5
								1,80	241	32,1	9,1	4,5
								2,86	382	50,9	13,1	6,7

  

2:1	额定载重 Load	额定速度 Speed	曳引轮 Sheave				额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V
			Ø	宽度 Width	n°	槽距 Pitch						
	kg	m/s	mm	mm		mm	Nm	kW	RPM	Hz	A	A
320	0,40	0,40	85	55	2	65	43	0,81	180	24,0	5,6	2,7
								1,01	225	30,0	5,6	2,7
								1,28	283	37,7	8,0	4,3
								2,03	449	59,9		5,6
400	0,40	0,50	85	55	2	65	54	1,01	180	24,0	6,9	3,4
								1,27	225	30,0	6,9	3,4
								1,60	283	37,7	10,0	5,4
								2,54	449	59,9		6,9
450	0,40	0,50	85	55	2	65	61	1,14	180	24,0	7,8	3,9
								1,43	225	30,0	7,8	3,9
								1,80	283	37,7	11,2	6,1
								2,85	449	59,9		7,8

