



主轴静载  
**static load**  
2000 kg

最大载重  
**load**  
450 kg

最大速度  
**speed**  
up to 1 m/s

曳引轮  
**sheave**  
85 - 100 mm

自重  
**weight**  
95 kg

额定扭矩 <b>Nominal Torque</b>	极数 <b>Poles</b>	编码器 <b>Encoder</b>	钢带轮 <b>Belt Pulley</b>		
			宽度 Width	钢带数 min - max	槽距 Pitch
<b>Nm</b>			mm	n°	mm
<b>74 S5 - 25% ED 180 s/h</b>	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531	60 55	2	260
<b>制动器 Brake</b>					
EMFR DC110V/1.4A[2X125Nm] EMFS125 2XDC110V/2X0.76A[2X135N.m] CE Certified					

- 1 - 以上数据是以平衡系数为45%的基础上计算出来的理论数据  
1 - The values are obtained considering system balanced at the 45%  
2 - 数据如有更改，恕不另行通知  
2 - Data are subject to change without prior notice

2:1	额定载重 Load	额定速度 Speed	曳引轮 Sheave				额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V								
			∅	宽度 Width	n°	槽距 Pitch														
	kg	m/s	mm	mm		mm	Nm	kW	RPM	Hz	A	A								
320	320	0,40	100	60	2	260	51	0,81	153	20,4	5,1	3,3								
		0,50						1,02	191	25,5	6,5	3,3								
		0,63						1,28	241	32,1	7,1	3,3								
		1,00						2,03	382	50,9	9,4	5,1								
400	400	0,40					100	60	2	260	66	1,05	153	20,4	6,6	4,3				
		0,50										1,32	191	25,5	6,6	4,3				
		0,63										1,66	241	32,1	8,5	4,3				
		1,00										2,63	382	50,9	12,2	6,6				
450	450	0,40									100	60	2	260	71	1,14	153	20,4	7,1	4,5
		0,50														1,43	191	25,5	9,1	4,5
		0,63														1,80	241	32,1	9,1	4,5
		1,00														2,86	382	50,9	13,1	6,7

  

2:1	额定载重 Load	额定速度 Speed	曳引轮 Sheave				额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V								
			∅	宽度 Width	n°	槽距 Pitch														
	kg	m/s	mm	mm		mm	Nm	kW	RPM	Hz	A	A								
320	320	0,40	85	55	2	260	43	0,81	180	24,0	5,6	2,7								
		0,50						1,01	225	30,0	5,6	2,7								
		0,63						1,28	283	37,7	8,0	4,3								
		1,00						2,03	449	59,9	5,6	5,6								
400	400	0,40					85	55	2	260	54	1,01	180	24,0	6,9	3,4				
		0,50										1,27	225	30,0	6,9	3,4				
		0,63										1,60	283	37,7	10,0	5,4				
		1,00										2,54	449	59,9	6,9	6,9				
450	450	0,40									85	55	2	260	61	1,14	180	24,0	7,8	3,9
		0,50														1,43	225	30,0	7,8	3,9
		0,63														1,80	283	37,7	11,2	6,1
		1,00														2,85	449	59,9	7,8	7,8

