

主轴静载
static load
2000 kg


最大载重
load
450 kg

最大速度
speed
up to 0,4 m/s

曳引轮
sheave
120 - 160 mm

自重
weight
80 kg

额定扭矩 Nominal Torque	极数 Poles	编码器 Encoder
Nm		
125 S5-25%ED 180s/h	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531
制动器 Brake		
EMFR DC110V/1.4A[2X125Nm]		

		绳槽 Ropes			
		曳引轮直径 ØD	宽度 F	绳径 Ø	绳槽数 n°
mm		mm		mm	
120	82	6,5	6	10	
160		6			



2:1	额定载重 Load	额定速度 Speed	∅	绳槽 Ropes	槽距 Pitch	额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V
	kg	m/s	mm	max	mm	Nm	kW	RPM	Hz	A	A
320	320	0,3	160	6x∅6	10	70	0,52	72	9,5	4,7	3,3
		0,4	160	6x∅6	10	81	0,81	95	12,7	5,5	3,9
400	400	0,3	160	6x∅6	10	103	0,77	72	9,5	7,0	4,9
		0,4	160	6x∅6	10	103	1,02	95	12,6	7,0	4,9
450	450	0,3	120	6x∅6.5	10	86	0,86	95	12,7	5,8	4,1
		0,4	120	6x∅6.5	10	86	1,14	127	16,9	6,9	5,8

1 - 数据如有更改，恕不另行通知

1 - Data are subject to change without prior notice

2 - 的曳引轮只适用于布鲁格CTP6.5MM钢丝绳

2 - Traction Sheave 120 mm available only for BRUGG CTP 6.5mm

