


主轴静载  
Static Load

自重  
Weight | 677 kg

额定扭矩 <b>Nominal Torque</b>	极数 <b>Poles</b>	编码器 <b>Encoder</b>
<b>Nm</b>		
<b>1620 S5 - 40% ED 180 s/h</b>	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531
<b>制动器 Brake</b>		
RSR1500 [2x1700Nm] 2X165W - 207V <sub>DC</sub>		

		绳槽 Ropes			尺寸 Dimensions
曳引轮直径 ØD	宽度 F	绳径 Ø	绳槽数 n°	槽距 Pitch	A
mm	mm	mm	max	mm	mm
320	180	8	10	17	153
400		10			

- 1 - 数据如有更改，恕不另行通知  
1 - Data are subject to change without prior notice.  
2 - 我们能够提供带电源线和不带电源线两种配置的机器  
2 - We are able to offer machines with both power cable and no power cable configurations.



2:1	额定载重	额定速度	Ø	绳槽	槽距	额定扭矩	额定功率	额定转速	额定频率	额定电流
	Load	Speed	mm	Ropes	Pitch	Torque	Power	RPM	Freq.	Current 380V
	kg	m/s	mm	max	mm	Nm	kW	RPM	Hz	A
2500	0,63	320	10xØ8	17	1228	9,7	75	10,0	31,8	
	0,63	400	10xØ10	17	1535	9,7	60	8,0	39,8	
	1,0	320	10xØ8	17	1228	15,4	119	15,9	35,6	
	1,0	400	10xØ10	17	1535	15,4	95	12,7	39,8	
	1,6	320	10xØ8	17	1228	24,6	191	25,5	51,5	
	1,6	400	10xØ10	17	1535	24,6	153	20,4	64,4	
	2,0	320	10xØ8	17	1228	30,7	239	31,8	64,4	
	2,0	400	10xØ10	17	1535	30,7	191	25,5	64,4	
	2,5	320	10xØ8	17	1228	38,4	298	39,8	85,7	
	2,5	400	10xØ10	17	1535	38,4	239	31,8	80,5	
3000	3,0	400	10xØ10	17	1535	46,1	286	38,2	107,1	
	0,63	320	10xØ8	17	1459	11,5	75	10,0	37,8	
	1,0	320	10xØ8	17	1459	18,2	119	15,9	42,3	
	1,6	320	10xØ8	17	1459	29,2	191	25,5	61,2	
	2,0	320	10xØ8	17	1459	36,5	239	31,8	76,5	
	2,5	320	10xØ8	17	1459	45,6	298	39,8	101,8	

