



主轴静载
static load
2000 kg

最大载重
load
450 kg

最大速度
speed
up to 1 m/s

曳引轮
sheave
240 mm

自重
weight
120 kg

额定扭矩 Nominal Torque	极数 Poles	编码器 Encoder
Nm		
215 S5-25%ED 180s/h	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531
制动器 Brake		
EMFR DC110V/1.9A[2X200Nm]		

		绳槽 Ropes		
曳引轮直径 ØD	宽度 F	绳径 Ø	绳槽数 n°	槽距 Pitch
mm		mm		mm
240	80	8	3-6	12



2:1	额定载重 Load	额定速度 Speed	∅	绳槽 Ropes	槽距 Pitch	额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V
	kg	m/s	mm	max	mm	Nm	kW	RPM	Hz	A	A
260		0,3	240	3x∅8	12	85	0,43	48	6,4	4,1	2,0
		0,4	240	3x∅8	12	85	0,57	64	8,5	4,1	2,0
320		0,3	240	3x∅8	12	122	0,61	48	6,4	5,8	2,8
		0,4	240	3x∅8	12	122	0,81	64	8,5	5,8	2,8
		0,5	240	3x∅8	12	122	1,02	80	10,6	7,0	3,4
400		0,3	240	3x∅8	12	131	0,65	48	6,4	6,3	3,0
		0,4	240	3x∅8	12	152	1,02	64	8,5	7,3	3,5
		0,5	240	3x∅8	12	152	1,27	80	10,6	7,3	3,5
		1,0	240	3x∅8	12	152	2,54	159	21,2	14,2	6,5
450		0,4	240	4x∅8	12	147	0,98	64	8,5	7,0	3,4
		0,5	240	4x∅8	12	171	1,43	80	10,6	8,2	4,8
		1,0	240	4x∅8	12	171	2,86	159	21,2	16,0	7,3

1 - 数据如有更改，恕不另行通知

1 - Data are subject to change without prior notice.

2 - 我们能够提供带电源线和不带电源线两种配置的机器

2 - We are able to offer machines with both power cable and no power cable configurations.

