



主轴静载
static load
2000 kg

最大载重
load
630 kg

最大速度
speed
up to 1 m/s

曳引轮
sheave
100 mm

自重
weight
120 kg

额定扭矩 Nominal Torque	阻转转矩 Short circuited torque	级数 Poles	编码器 Encoder	钢带轮 Belt Pulley		
				宽度 Width	钢带数 min - max	槽距 Pitch
Nm	Nm			mm	n°	mm
104 S5 - 40% ED 180 s/h	140	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531	60	3	65
制动器 Brake						
EMFR DC110V/1.4A[2X125Nm]						



2:1	额定载重 Load		曳引轮 Traction sheave				额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current	额定电流	
	kg		m/s	∅	宽度 Width	n°					槽距 Pitch	220V	380V
				mm	mm						mm	Nm	kW
630	0,4	100	60	3	65	100					8,4	4,8	
	0,5										11,4	6,7	
	1,0										16,2	8,3	

1:1	额定载重 Load		曳引轮 Traction sheave				额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current	额定电流	
	kg		m/s	∅	宽度 Width	n°					槽距 Pitch	220V	380V
				mm	mm						mm	Nm	kW
400	0,63	100	60	3	65	115					10,0	5,5	
	1,00										10,0	5,5	

1 - 数据如有更改，恕不另行通知
1 - Data are subject to change without prior notice

