



主轴静载
static load
1250 kg


最大载重
load
450 kg

最大速度
speed
up to 1 m/s

曳引轮
sheave
200 mm

自重
weight
75 kg

额定扭矩 Nominal Torque	阻转扭矩 Short circuited torque	级数 Poles	编码器 Encoder
Nm	Nm		
150 S5-25%ED 180s/h	170	16	ERN1387 ECN1313 EI53C9.25 TS5213N2531
制动器 Brake			
EMFR DC110V/2.0A[2X200Nm]			

		绳槽 Ropes		
曳引轮直径 ØD	宽度 F	绳径 Ø	绳槽数 n°	槽距 Pitch
mm		mm		mm
200	57	8	3-4	12
160		6	3-5	10

2:1	额定载重 Load		∅	绳槽 Ropes	槽距 Pitch	额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V
	kg	m/s	mm	max	mm	Nm	kW	RPM	Hz	A	A
260	260	0,3	200	3x∅8	12	71	0,43	57	7,6	4,2	2,6
		0,4	200	3x∅8	12	71	0,57	76	10,2	4,2	2,6
320	320	0,3	200	3x∅8	12	87	0,52	57	7,6	5,8	3,3
		0,4	200	3x∅8	12	87	0,70	76	10,2	5,8	3,3
		0,5	200	3x∅8	12	87	0,87	95	12,7	5,8	3,3
400	400	0,4	200	3x∅8	12	109	0,87	76	10,2	6,4	4,0
		0,5	200	3x∅8	12	109	1,09	95	12,7	8,9	4,0
		1,0	200	3x∅8	12	109	2,18	191	25,5	13,3	6,9
450	450	1,0	200	4x∅8	12	143	2,86	191	25,5	17,4	9,0

2:1	额定载重 Load		∅	绳槽 Ropes	槽距 Pitch	额定扭矩 Torque	额定功率 Power	额定转速 RPM	额定频率 Freq.	额定电流 Current 220V	额定电流 Current 380V
	kg	m/s	mm	max	mm	Nm	kW	RPM	Hz	A	A
260	260	0,3	160	5x∅6	10	57	0,43	72	9,5	3,7	2,1
		0,4	160	5x∅6	10	57	0,57	95	12,7	4,2	2,1
320	320	0,3	160	5x∅6	10	70	0,52	72	9,5	4,5	2,6
		0,4	160	5x∅6	10	70	0,70	95	12,7	5,1	2,6
		0,5	160	5x∅6	10	70	0,87	119	15,9	5,7	4,1
400	400	0,4	160	5x∅6	10	87	0,87	95	12,7	6,4	3,2
		0,5	160	5x∅6	10	87	1,09	119	15,9	7,1	5,7
		1,0	160	5x∅6	10	87	2,18	239	31,8	10,6	5,6
450	450	0,4	160	5x∅6	10	98	0,98	95	12,7	7,2	3,6
		0,5	160	5x∅6	10	98	1,23	119	15,9	8,0	6,4
		1,0	160	5x∅6	10	98	2,45	239	31,8	12,0	6,3

- 1 - 数据如有更改，恕不另行通知
1 - Data are subject to change without prior notice
- 2 - 我们能够提供带电源线和不带电源线两种配置的机器
2 - We are able to offer machines with and without power cable configurations.

